Fujitsu recommends Windows 8 Pro.



Data Sheet Fujitsu ESPRIMO PH300 E85+ Desktop PC

Your Immediately Available Multimedia PC

The Fujitsu ESPRIMO PH300 E85+ is equipped with the latest Intel® technology including Hyper-Threading and Turbo Boost functionality. This solid performer provides a timeless design fitting perfectly into your home environment. The Fujitsu ESPRIMO PH300 E85+ is available from your dealer at all times and is thus an ideal choice for quick purchase decisions.

Intelligent performance

The ideal PC for the day-to-day challenges of office life

■ 3rd generation Intel® Core[™] i3, Core[™] i5, and Core[™] i7 processors

Designed and engineered in Germany

Outstanding quality and stable functions based on German production standards

■ The development, production and function tests are all under one roof in Germany

Multimedia experience

Enjoy high-definition multimedia and entertainment

Optional with powerful NVIDIA® GeForce® GT 420 with 1 GB or 2 GB VRAM for graphically rich content, quick transfer of photos with the integrated multi card reader









Components

Drocossor	Intel® Core™ i7-3770 processor (4 Cores / 8 Threads, 3.40 GHz, up to 3.9 GHz, 8 MB, Intel® HD Graphics 4000) *
Processor	Intel® Core™ i5-3470 processor (4 Cores / 8 Threads, 3.40 GHz, up to 3.9 GHz, 8 MB, Intel® HD Graphics 4000) * Intel® Core™ i5-3470 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 2500) *
	Intel® Core™ i5-3330 processor (4 Cores / 4 Threads, 3.00 GHz, up to 3.2 GHz, 6 MB, Intel® HD Graphics 2500)
	Intel® Core™ i3-3220 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2500)
	Intel® Core™ i3-2130 processor (2 Cores / 4 Threads, 3.40 GHz, 3 MB, Intel® HD Graphics 2000)
	Intel® Pentium® processor G870 (2 Cores / 2 Threads, 3.10 GHz, 3 MB, Intel® HD Graphics)
	Intel® Pentium® processor G645 (2 Cores / 2 Threads, 2.90 GHz, 3 MB, Intel® HD Graphics)
	Intel® Pentium® processor G2120 (2 Cores / 2 Threads, 3.10 GHz, 3 MB, Intel® HD Graphics)
	Intel® Pentium® processor G2020 (2 Cores / 2 Threads, 2.90 GHz, 3 MB, Intel® HD Graphics)
	Intel® Celeron® processor G1610 (2 Cores / 2 Threads, 2.60 GHz, 2 MB, Intel® HD Graphics)
	*with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)
perating systems	
perating system	Windows 8
	Windows® 7 Home Premium 64-bit
	Windows® 7 Home Basic (EM) 32-bit
Operating system compatible	openSUSE Linux
perating system notes	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com
Nemory modules	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
,	4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
ard disk drives (internal)	HDD SATA III, 7200 rpm, 2000 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
lard disk notes	Up to 20 GB of HDD space is reserved for system recovery
raphics	NVIDIA® GeForce® GT630 DisplayPort 2GB FH, 2 GB
	NVIDIA® GeForce® 605 DisplayPort 1GB FH, 1 GB
	ATI Radeon® HD7350 1GB FH, 1 GB
rives (optional)	DVD Super Multi
onves (optional)	MCR 24in1 & USB 3.0 front con., 3.5"
	MultiCard Reader 24in1 USB 2.0 3.5"
nterface add on cards/components	
optional)	WLAN III, 802.11g/Draft-n (Windows only, dedicated regions only)
	USB 3.0 PCIe x1
ase unit	ESPRIMO PH300 E85+
1ainboard	
lainboard type	D2990
ormfactor	μATX
hipset	Intel® H61
Processor socket	LGA 1155
rocessor quantity maximum	1
Memory slots	2 DIMM (DDR3)
Supported capacity RAM (max.)	8 GB
Memory frequency	1333 MHz

Page 2 / 7 www.fujitsu.com/fts/ESPRIMO

 Mainboard	
Memory notes	Dual channel support.
	For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
.AN	10/100/1000 MBit/s Realtek RTL 8111E
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software
bios leatures	Recovery BIOS
	Unified Extensible Firmware Interface (UEFI)
Audio codec	Realtek ALC663
Audio features	5.1 surround sound
/O controller on board	
Serial ATA total	4
Controller functions	Serial ATA II (3 Gbit)
controller functions	NCQ
	AHCI
nterfaces	
Interraces Audio: line-in	1
	1
Audio: line-in / microphone Audio: line-out	<u> </u>
	·
Front audio: microphone	1
Front audio: headphone	1
JSB 2.0 total	8
JSB front	2
JSB rear	4
JSB internal	2
/GA	1
DVI	1 (DVI-D)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
nput device / components	
· · · · · · · · · · · · · · · · · · ·	Optical USB wheel mouse
	Keyboard
Orive bays	
Orive bays total	5
3.5-inch internal bays	2
3.5-inch external bays	1
5.25-inch external bays	2
·	
Slots	1 x (210 mm / 8.27 inch) Full height
PCI-Express 2.0 x16	2 x (190 mm / 7.48 inch) Full height
PCI-Express x1	2 X (130 Hilli / 7.46 Hich) run neignt
Graphics on board	
Graphics brand name	Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU)
hared video memory	up to 1759 MB
TFT resolution (VGA)	1024 x 768 pixel
	1280 x 1024 pixel
	1360 x 768 pixel
	1440 x 900 pixel
	1600 x 900 pixel 1600 x 1200 pixel
	1680 x 1200 pixel
	1920 x 1030 pixel
	[47][x 1][8][n]xe[

Page 3 / 7 www.fujitsu.com/fts/ESPRIMO

Graphics on board	
TFT resolution (DVI)	1360 x 768 pixel
	1440 x 900 pixel
	1600 x 900 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel 1920 x 1200 pixel
Craphics features	
Graphics features	Dual display support DirectX® 10.1 or DirectX® 11 (depending on CPU)
	HDCP support
	Open GL® 3.3 (depending on CPU)
	Open CL™ 1.1 (depending on CPU)
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible
enephines instess	Shared memory depending on main memory size and operating system
	Resolution (color depth up to 32 Bit/pixel)
	For TFT we recommend using 60Hz
Electrical values	
Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 83% / 86% / 85%
•	0-Watt mode with hard-off switch
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	330 W
Power factor correction/active power	active
Monitor outlet	No
Power consumption	
Heat dissipation	
Heat dissipation notes	See white paper Energy Consumption
Noise for standard configuration (HDD,	ODD)
Noise emission	According to ISO9296
Related Processors for noise	Intel® Core™ i5 2400
Noise Operation mode 1: ODD load	5.0 B/ 36 dB(A)
(Blue angel requirement)	
Noise Operation mode 2: HDD load	3.7 B/ 23 dB(A)
(Blue angel requirement)	
Noise Operation mode 3: CPU 90% load	3.9 B/ 27 dB(A)
(Blue angel requirement)	
Noise Operation mode 4: High load	4.2 B/ 27 dB(A)
Noise Operation mode 5: Office	3.7 B/ 22 dB(A)
applications 2.0	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
Idle mode (Blue Angel requirement)	3.7 B/ 22 dB(A)
Noise notes	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position
Dimensions / Weight / Environmental	
Dimensions (W \times D \times H)	175 x 425 x 353 mm
	6.89 x 16.74 x 13.9 inch
Operating position	Vertical
Weight	9 kg
Weight (lbs)	20.22 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 ℃ (50 - 95 °F)
, , , , , , , , , , , , , , , , , , , ,	•

Page 4 / 7 www.fujitsu.com/fts/ESPRIMO

Compliance	
Compliance Product	ESPRIMO PH300
Model	MI4W-2990
Europe	(E
Global	RoHS (Restriction of hazardous substances)
diodai	WEEE (Waste electrical and electronic equipment)
	Microsoft Operating Systems (HCT / HCL entry / WHQL)
	ENERGY STAR®
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/
Additional Software	
Additional software (preinstalled)	Adobe® Reader®
(premisere)	Norton Internet Security (incl. Firewall) 60 days version
	Win7: Fujitsu Recovery (Hard Disk Based Recovery)
	Win8: Microsoft Push Button Recovery (Hard Disk Based Recovery)
	Don't forget Office.
Additional software (optional)	Recovery DVD for Windows®
	Drivers & Utilities DVD (DUDVD)
	CyberLink PowerDVD (BD/DVD playback software for Blu-ray Disc™)
	CyberLink PowerDVD (DVD playback software)
	Nero Essentials XL
Miscellaneous	
Compatibility (references)	
	DMI 2.0
	PC 2001
	WMI 1.5
	USB 2.0
	SMBIOS
Manageability	
Manageability technology	DeskUpdate Driver management
	PXE 2.1 Boot code
	Wake up from S5 (off mode)
	WoL (Wake on LAN)
Security	
System protection	Kensington Lock support
	Eye for padlock
Audit proof protection	Boot sector virus protection Control of external interfaces
Assess probables	
Access protection	User and supervisor BIOS password Optional: Access protection via external SmartCard reader
Declarate information	approximative protection the external situated a reducti
Packaging information	E/O v 200 v E00 mm
Packaging dimension (mm)	540 x 290 x 500 mm
Packaging dimension (inch)	21.26 x 11.42 x 19.69 inch
Max. quantity / pallet	24
Material - Weight (g) Carton	1270 g
Material - Weight (lbs) Carton	2.8 lbs
Material - Weight (g) EPS / PS	160 g
Material - Weight (lbs) EPS / PS	0.35 lbs
Material - Weight (g) PE	60 g
Material - Weight (lbs) PE	0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process
Warranty	
Standard Warranty	1 year / 2 years (depending on country)
Standard Warranty	ו אָבטו / ב אָבטוּ (עבּיְבְּרוּטוווטַ טוו נטטוונוץ)

Page 5 / 7 www.fujitsu.com/fts/ESPRIMO

Warranty	
Service level	Collect & Return Service (for countries within region FTS CEMEA&I, for all other countries depending on local regulations, minimum: 1 year material warranty)
Warranty Terms & Conditions Maintenance and Support Services	http://support.ts.fujitsu.com/warranty - the perfect extension
Recommended Service	9x5, Response Time: Next Business Day
Spare Parts availability	3 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

CELVIN® Drive D100



The CELVIN® Drive D100 is a highly reliable external storage device with a S26341-F103-L118 also easy to set up additional home network capacity by connecting it with dedicated routers or NAS devices.

HS E2000 Communicator Headset



The Fujitsu HS E2000 Communicator headset allows you to use your personal computer for Voice over IP (VoIP) in stereo audio quality. This premium headset is designed to provide superb audio quality and comfort for the telephony, internet chat, speech recognition, video conferencing and multimedia applications.

Order Code: S26391-F7139-L5

Wireless Keyboard Set LX900



The Wireless Keyboard LX900 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set with offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption for security.

S26381-K564-L4** (**: Country specific variation)

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu ESPRIMO PH300 E85+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO PH300 E85+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at http://www.fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions Website: www.fujitsu.com/fts 2013-02-27 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

Copyright © Fujitsu Technology Solutions